




Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1.	Product identifier	
	Trade name:	BIOMOUNT HIGH
	Chemical name:	-
	Catalogue number:	BMTH-X**
1.2.	Relevant identified uses of the substance or mixture and uses advised against	
	Uses:	Very high viscosity xylene-based medium for permanent covering of microscope slides and mounting cover slips.
	Uses advised against:	Only the identified uses are advised.
	Reason why uses advised against:	The product is intended for use only as an <i>in vitro</i> diagnostic medical device, registered at the Agency for Medicinal Products and Medical Devices and there is no reason to use it for other purposes.
1.3.	Details of the supplier of the safety data sheet	
	Supplier:	BioGnost Ltd.
	Address:	Medjugorska 59, Zagreb
	Telephone number:	+385 1 2409997
	Telefax:	+385 1 2404039
	e-mail of competent person:	msds@biognost.hr
	National contact:	-
1.4.	Emergency telephone numbers	
	National Protection and Rescue Directorate:	112
	Medical information:	+385 1 2348 342
	Other information:	-

SECTION 2. HAZARDS IDENTIFICATION		
2.1.	Classification of the substance or mixture	
2.1.1.	Classification according to Regulation (EC) No 1272/2008 (CLP)	
	Hazard class and category code:	Hazard statement*:
	Flam. Liq. 3	H226
	Asp. Tox. 1	H304
	Acute Tox. 4	H312
	Acute Tox. 4	H332
	Eye Irrit. 2	H319
	STOT RE 2	H373
2.1.2.	Additional information	
	-	
* For full text of Hazard- and EU Hazard-statements: see SECTION 16		
2.2.	Label elements	

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

Product identification:	BIOMOUNT HIGH
Identification number:	-
Authorisation number:	-
Hazard pictograms:	 GHS02  GHS07  GHS08
Signal word:	Danger
Hazard statement:	H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H312+H332 Harmful in contact with skin or if inhaled. H319 Causes serious eye irritation. H373 May cause damage to organs through prolonged or repeated exposure.
Precautionary statements:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/protective clothing/eye/protection/face protection. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308+P313 IF exposed or concerned: Get medical advice/attention.
Supplemental hazard information (EU):	-
2.3. Other hazards	-

SECTION 3. Composition/information on ingredients

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

CAS/ EC/ Index number	REACH Registration No	Weight % content (or range)	Identification name	Classification according to Regulation (EC) No 1272/2008 (CLP)
1330-20-7/ 215-535-7/ 601-022-00-9	01-2119488216-32- XXXX	≥ 40 %	xylene	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4 ; H312 Acute Tox. 4, H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373

SECTION 4. First aid measures		
4.1.	Description of first aid measures	
	General notes:	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Immediately remove any clothing soiled by the product.
	Following inhalation:	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
	Following skin contact:	Remove contaminated clothing. Immediately wash with plenty of water and soap and rinse thoroughly. If symptoms persist, consult a doctor.
	Following eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
	Following ingestion:	DO NOT induce vomiting. If symptoms persist, consult a doctor.
	Self-protection of the first aider	Avoid direct contact with the chemical; use appropriate protective equipment described in Section 8.
4.2.	Most important symptoms and effects, both acute and delayed	
	Following inhalation:	High concentration vapor inhalation may cause headache, dizziness, difficult breathing and unconsciousness.
	Following skin contact:	Causes skin irritation, redness, swelling. Prolonged or repeated contact causes defatting and dry skin.
	Following eye contact:	Vapors irritate eyes. Splashing may cause irritation and redness.
	Following ingestion:	Nausea, vomiting (danger of aspiration), diarrhoea. Aspiration may cause headache, vertigo, nausea, dazed feeling-unconsciousness/coma, possible hypothermia, reactions to the heart/circulatory system such as vasodilation (flush), hypotension, arrhythmia (possible ventricular fibrillation through cardiac sensitization), danger of central respiratory paralysis or of cardiac arrest; functional disturbance to the liver and kidneys and persistent disturbance to the CNS as sequelae.
4.3.	Indication of any immediate medical attention and special treatment needed	

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

No further relevant information available.
--

SECTION 5. Firefighting measures		
5.1.	Extinguishing media	
	Suitable extinguishing media:	CO ₂ , powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
	Unsuitable extinguishing media:	water with full jet
5.2.	Special hazards arising from the substance or mixture	
	Hazardous by products of fire:	Formation of toxic gases is possible during heating or in case of fire.
5.3.	Advice for firefighters	
	Use a self-contained open-circuit compressed air breathing apparatus and fireproof clothing.	
5.4.	Additional information	
	Collect contaminated firefighting water separately. Do not contaminate the environment with extinguishing media.	

SECTION 6. Accidental release measures		
6.1.	Personal precautions, protective equipment and emergency procedures	
6.1.1.	For non-emergency personnel	
	Protective equipment:	Use personal protective equipment (see Section 8). Keep unprotected persons away.
	Accident prevention methods:	Evacuate members of all non-essential personnel and those members without protective equipment. Do not breathe in vapor, ensure adequate ventilation and avoid contact with skin and eyes. Remove all sources of sparks and ignition. Do not smoke.
	Emergency procedures:	Mark the area using proper signs.
6.1.2.	For emergency responders:	
	Use protective equipment; in case of inadequate ventilation use adequate airways protective equipment (see Section 8).	
6.2.	Environmental precautions:	
	Do not dispose of in sewage, drainage system and waterways. In case of large spillage contact National Protection and Rescue Directorate (NPRD) on 112.	
6.3.	Methods and materials for containment and cleaning up	
6.3.1.	Bunding, covering of drains; capping procedures:	Sand or clay barriers.

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

6.3.2.	Cleaning up:	Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place the waste material in tightly closed impermeable containers. Store the substance in well ventilated storage rooms until disposal. Submit for disposal to the legal persons authorized by the Ministry of Environmental and Nature Protection. After disposal of the products, wash the area and involved materials with water.
6.3.3.	Other information:	Do not use tools that may cause sparks.
6.4.	Reference to other sections	
	See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.	

SECTION 7. Handling and storage		
7.1.	Precautions for safe handling	
7.1.1.	Protection measures	
	Measures to prevent fire:	Use in well ventilated storage rooms. Keep away from sources of heat and ignition. Carry out measures for preventing static electricity.
	Measures to prevent aerosol and dust generation:	Secure proper ventilation.
	Measures to protect the environment:	Prevent spilling into the sewage system and waterways.
	Other measures:	-
7.1.2.	Advice on general occupational hygiene:	
	Do not eat, drink or smoke in the workspace. Thoroughly wash hands after work and before eating.	
7.2.	Conditions for safe storage, including any incompatibilities	
	Technical measures and storage conditions:	Keep in tightly closed and upright set containers in a well ventilated storage rooms, and away from sources of heat, sunlight, and other incompatible substances.
	Packaging materials:	Manufacturer's original packaging.
	Requirements for storage rooms and vessels:	Keep away from food and drink. Keep the containers tightly closed.
	Advices for storage equipment:	The storage must be made of hard material; floors must be resistant to chemicals. There must be no drain that directly leads into sewage system. Secure proper ventilation.
	Further information on storage conditions:	Do not place the unused material in the storage room and do not use empty containers for storing other chemicals. Do not store with incompatible materials (see Section 10).
7.3.	Specific end use(s)	

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

Recommendations:	-
Industrial sector specific solutions:	-

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Substance	CAS No	Occupational exposure limit values/short term values		Biological limit values
		ppm	mg/m ³	
Xylene (all isomers)	1330-20-7	50/100	220/440	1.50 mg/L (14.13 µmol/L) xylene, blood, end of shift 1.50 g/g (0.88 mol/mol) creatinine (methyl hippuric acid, urine, end of shift)

Substance: -

EC No: - CAS No: -

DNEL

Industrial

Route of exposure:	Acute effect local	Acute effect systemic	Chronic effect local	Chronic effect systemic
Oral	-	-	-	-
Inhalation	289 mg/m ³ (xylene)	-	-	77 mg/m ³ (xylene)
Dermal	-	-	-	180 mg/kg (xylene)

Critical physical parameters: solubility, flammability, corrosivity: -

Consumer

Route of exposure:	Acute effect local	Acute effect systemic	Chronic effect local	Chronic effect systemic
Oral	-	-	-	-
Inhalation	174 mg/m ³ (xylene)	-	-	14,8 mg/m ³ (xylene)
Dermal	-	-	-	108 mg/kg (xylene)

PNEC

Environmental protection target	PNEC
Fresh water	0.327 mg/l (xylene)
Freshwater sediments	12.46 mg/kg (xylene)
Marine water	0.327 mg/l (xylene)
Marine sediments	12.46 mg/kg (xylene)

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

Food chain	0.327 mg/l (xylene)
Microorganisms in sewage treatment	6.58 mg/l (xylene)
Soil (agricultural)	2.31 mg/kg (xylene)
Air	No information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Substance/mixture related measures to prevent exposure during identified uses:	Use personal protective equipment. Do not eat, drink or smoke in the workspace.
Structural measures to prevent exposure:	No information available
Organisational measures to prevent exposure:	Organization of work in order to reduce other worker's influence during work process.
Technical measures to prevent exposure:	Secure proper workspace ventilation in order to keep concentration levels in air below permitted levels.

8.2.2. Personal protection equipment:

8.2.2.1. Eye and face protection:	Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as EN 166(EU)
-----------------------------------	---

8.2.2.2. Skin protection

Hand protection:	<p>Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.</p> <p>Full contact:</p> <p>Glove material: Viton Glove thickness: 0.7 mm Break through time: 480 min</p> <p>Splash contact:</p> <p>Glove material: Nitrile rubber Glove thickness: 0.4 mm Break through time: 35 min</p>
Other skin protection:	Complete suit protecting against chemicals, flame retardant antistatic protective clothing (EN 13688). The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

8.2.2.3.	Respiratory protection:	Where risk assessment shows air-purifying respirators are appropriate use type ABEK (EN 14387) respirator cartridges as a backup to engine protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as CEN (EU).
8.2.2.4.	Thermal hazards:	No information available
8.2.3.	Environmental exposure controls	
	Substance/mixture related measures to prevent exposure:	See Section 6
	Structural measures to prevent exposure:	Use modern equipment.
	Organisational measures to prevent exposure:	Adapt the work process to the required working conditions of the workplace.
	Technical measures to prevent exposure:	See Section 6

SECTION 9. Physical and chemical properties

9.1.	Information on basic physical and chemical properties		
		Value	Method
	Physical state:	liquid	No information available
	Colour:	light yellow	No information available
	Odour:	aromatic	No information available
	Odour threshold:	No information available	No information available
	pH:	No information available	No information available
	Melting point / freezing point;	No information available	No information available
	Initial boiling point and boiling range:	No information available	No information available
	Flash point:	29 °C	No information available
	Evaporation rate:	No information available	No information available
	Flammability (solid, gas):	No information available	No information available
	Upper/lower flammability or explosive limits:	No information available	No information available
	Vapour pressure:	No information available	No information available
	Vapour density:	No information available	No information available
	Relative density	No information available	No information available
	Bulk density:	No information available	No information available
	Solubility(ies):	Insoluble in water	No information available
	Partition coefficient: n-octanol/water (log Pow):	No information available	No information available
	Auto-ignition temperature:	No information available	No information available

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

	Decomposition temperature:	No information available	No information available
	Viscosity:	No information available	No information available
	Explosive properties:	No information available	No information available
	Oxidising properties:	No information available	No information available
9.2.	Other information		
	-		

SECTION 10.: Stability and reactivity		
10.1.	Reactivity:	No relevant information available.
10.2.	Chemical stability:	The product is chemically stable under recommended storage conditions.
10.3.	Possibility of hazardous reactions:	No dangerous reactions known.
10.4.	Conditions to avoid:	Sources of heat, flames and sparks.
10.5.	Incompatible materials:	Strong oxidizing agents.
10.6.	Hazardous decomposition products:	Carbon monoxide.

SECTION 11. Toxicological information					
11.1. Information on toxicological effects					
Acute toxicity:					
Route of exposure:	Method	Species	Effective Dose LD ₅₀ /LC ₅₀ or ATE _{mixture}	Exposure time	Results
Oral:	No information available	rat	LD ₅₀	No information available	3.523 mg/kg (xylene)
Dermal:	No information available	rabbit	LD ₅₀	No information available	1.134 mg/kg (xylene)
Inhalation:	No information available	rat	LC ₅₀	4 h	11.,23 mg/l (xylene)
Specific target organ toxicity - single exposure (STOT-SE):					
	Specific effects		Target organ		Note
Oral:	No information available		No information available		-
Dermal:	No information available		No information available		-
Inhalation:	No information available		Respiratory system		May cause respiratory irritation
Aspiration hazard:					
			May cause respiratory irritation. May be fatal if swallowed and enters respiratory system.		

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

Irritation and corrosion						
	Exposure time	Species	Evaluation	Method	Note	
Skin corrosion/irritation	24h	rabbit (xylene)	-	-	Causes skin irritation.	
Serious eye damage/irritation	-	-	-	-	No information available	
Sensitization						
Skin sensitization:	No information available					
Respiratory sensitization:	No information available					
Symptoms related to physical, chemical, and toxicological properties						
Oral exposure:	Nausea, vomiting (danger of aspiration), diarrhoea. Aspiration may cause headache, vertigo, nausea, dazed feeling-unconsciousness/coma, possible hypothermia, reactions to the heart/circulatory system such as vasodilation (flush), hypotension, arrhythmia (possible ventricular fibrillation through cardiac sensitization), danger of central respiratory paralysis or of cardiac arrest; functional disturbance to the liver and kidneys and persistent disturbance to the CNS as sequelae.					
Dermal exposure:	Causes skin irritation, redness, swelling. Prolonged or repeated contact causes defatting and dry skin.					
Inhalation exposure:	Vapor inhalation may cause nose and throat irritation followed by sore throat, cough, difficult breathing and suffocating. High concentration vapor inhalation may cause headache, malaise and fatigue, difficult breathing, chest tightness, coordination and CNS disorders.					
Eye exposure:	Vapors irritate eyes. Splashing may cause irritation and redness, lacrimation, pain, swelling, blurred vision, photophobia.					
Repeated dose toxicity (subacute, subchronic, chronic)						
	Dose	Exposure time	Species	Method	Evaluation	Note
Subacute oral	No information available	No information available	No information available	No information available	No information available	-
Subacute dermal	No information available	No information available	No information available	No information available	No information available	-
Subacute inhalation	No information available	No information available	No information available	No information available	No information available	-

Trade name:	BIOMOUNT HIGH					
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4	

Subchronic oral	No information available	No information available	No information available	No information available	No information available	-
Subchronic dermal	No information available	No information available	No information available	No information available	No information available	-
Subchronic inhalation	No information available	No information available	No information available	No information available	No information available	-
Chronic oral	No information available	No information available	No information available	No information available	No information available	-
Chronic dermal	No information available	No information available	No information available	No information available	No information available	-
Chronic inhalation	No information available	No information available	No information available	No information available	No information available	-

Specific target organ toxicity - repeated exposure (STOT-RE):

	Specific effects	Target organ	Note
Subacute oral	No information available	No information available	-
Subacute dermal	No information available	No information available	-
Subacute inhalation	No information available	No information available	-
Subchronic oral	No information available	No information available	-
Subchronic dermal	No information available	No information available	-
Subchronic inhalation	No information available	No information available	-
Chronic oral	No information available	No information available	-
Chronic dermal	No information available	No information available	-
Chronic inhalation	No information available	Central nervous system, liver, kidney	May cause damage to organs.

CMR effects (carcinogenicity, mutagenicity, reproductive toxicity)

Carcinogenicity:	No information available
Mutagenicity <i>in-vitro</i> :	No information available
Genotoxicity:	No information available
Mutagenicity <i>in-vivo</i> :	No information available
Germ cell mutagenicity :	No information available
Reproductive toxicity:	No information available

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

Summary of evaluation of the CMR properties:		No information available
11.2. Practical experiences:		
Classification observations:	No information available	
Other observations:	No information available	
11.3. General notes:		
-		

SECTION 12. Ecological information						
12.1. Toxicity						
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish	LC ₅₀	96 hours	Oncorhynchus mykiss (rainbow trout)	No information available	3.3 mg/l (xylene)	-
Crustacea:	EC ₅₀	48 hours	Daphnia magna	No information available	75.49 mg/l (xylene)	-
Algae/aquatic plants:	IC ₅₀	72 hours	Pseudokirchneriella subcapitata	No information available	72 mg/l (xylene)	-
Other organisms:	-	-	-	-	-	-
Chronic (long-term) toxicity	Doza	Exposure time	Species	Method	Evaluation	Note
Fish	LC ₅₀	96 hours	No information available	No information available	No information available	-
Crustacea:	EC ₅₀	48 hours	No information available	No information available	No information available	-
Algae/aquatic plants:	IC ₅₀	72 hours	No information available	No information available	No information available	-
Other organisms:	-	-	-	-	-	-
12.2. Persistence and degradability						
Abiotic degradation						

Trade name:	BIOMOUNT HIGH			
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version: 4

	Degradation half-lives	Method	Evaluation	Note
Marine water	No information available	No information available	No information available	-
Fresh water	No information available	No information available	No information available	-
Air	No information available	No information available	No information available	-
Soil	No information available	No information available	No information available	-

Biodegradation				
% Degradation	Time (days)	Method	Evaluation	Note
81% (DBP)	No information available	No information available	No information available	Readily biodegradable.

12.3. Bioaccumulative potential						
Octanol-water partition coefficient (log Kow)						
Value	Concentration	pH	°C	Method	Evaluation	Note
log Kow 2.95	No information available	-	-	No information available	No information available	xylene

Bioconcentration Factor (BCF)						
Value	Species	Method	Evaluation	Note		
-	-	No information available	-	-		

Chronic ecotoxicity						
Value	Dose	Exposure time	Species	Method	Evaluation	Note
Chronic toxicity on fish	LC ₅₀	No information available	No information available	No information available	No information available	-
Chronic toxicity on crustacea (Daphnia)	EC ₅₀	No information available	No information available	No information available	No information available	-

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

12.4. Mobility in soil					
Known or predicted distribution in environmental compartments:					
No information available					
Surface tension:					
	Value	°C	Concentration	Method	Note
	No information available	No information available	No information available	No information available	-
Adsorption / desorption					
Transport	A/D coefficient Henry's constant	log Kow	Evaporation rate	Method	Note
Soil-Water	No information available	No information available	No information available	No information available	-
Water-Air	No information available	No information available	No information available	No information available	-
Soil-Air	No information available	No information available	No information available	No information available	-
12.5. Results of PBT and vPvB assessment					
No information available					
12.6. Other adverse effects					
No information available					
SECTION 13. Disposal considerations					
13.1. Waste processing methods					
13.1.1. Product/Packaging disposal:					
Submit for disposal to the legal person authorized by the Ministry of Environmental and Nature Protection.					
13.1.2. Waste codes/waste designations according to Low:					
Disposal must be made according to official regulations.					
13.1.3. Waste treatment – relevant information					
No information available					

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

13.1.4.	Sewage disposal – relevant information:
	Waste must not be disposed of into the sewage system.
13.1.5.	Other disposal recommendations:
	Do not dispose of the product's remains into the sewage system. Submit the remains to the collectors authorized by the ministry in charge. Do not dispose of the packaging into the sewage system. Submit the packaging to the collectors authorized by the ministry in charge. Do not dispose of in places where ignition may occur.
13.1.6.	Relevant Community provisions:
	Disposal must be made according to official regulations.

SECTION 14. Transport information

Transporting/shipment by road (ADR)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by rail (RID)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by inland waterways (ADN)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transporting/shipment by sea (IMDG)	
UN number:	1307
UN proper shipping name:	Xylenes

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Transport in bulk condition in accordance with Annex II. of MARPOL 73/78 and IBC Codex:	-
Transporting/shipment by air (ICAO-TI/IATA-DGR)	
UN number:	1307
UN proper shipping name:	Xylenes
Transport hazard class(es):	3
Packing group:	III
Environmental hazards:	-
Special precautions for user:	-
Further information:	-

SECTION 15. Regulatory information	
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
	EU regulations
	Authorisation and/or restrictions on use
	Authorisations: -
	Restrictions: -
	Other EU regulations: EC Regulation No. 1906/2007 and EC Regulation No. 1272/2008 of the European Parliament and the European Council; The European Commission Regulation No. 453/2010 on changes and amendments to the Regulation (EC) No. 1907/2006 of the European Parliament and Council on registration, evaluation, authorization and restriction of chemical substances (REACH); EC Regulation No. 2037/2000 of the European Parliament and Council of 29 June 2000 on ozone-depleting substances; EC Regulation No. 689/2008 of the European Parliament and Council of 17 June 2008 concerning the export and import of dangerous chemicals; EC Regulation No. 850/2004 of the European Parliament and Council of 29 April 2004 on persistent organic pollutants; Directive 2008/98/EC of the European Parliament and Council of 19 November 2008 on waste and repealing certain Directives
	Information according 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline)

Trade name:	BIOMOUNT HIGH				
Product code:	BMTH-X**	Date of compilation:	17 June 2019	Version:	4

National legislation:	Chemicals Act, Regulation on classification, packaging and labeling of dangerous substances, Ordinance on occupational exposure limit values and on biological limit values, Regulation on categories, types and classification of waste with a waste catalog and list of hazardous waste, Ordinance on writing Material safety data sheet, Transport of Hazardous Substances Act
-----------------------	---

15.2.	Chemical safety assessment
	None

SECTION 16. Other information

16.1.	Indication of changes:	-
16.2.	Abbreviations and acronyms:	PBT Stable, bioaccumulative and toxic vPvB Strongly stable and strongly bioaccumulative LD ₅₀ Lethal dose, 50% LC ₅₀ Lethal concentration, 50% STOT – SE Specific target organ toxicity - single exposure
16.3.	Key literature references and source of data:	-
16.4.	Classification and procedure used to derive the classification for mixture according to Regulation (EC) 1272/2008 (CLP)	
	Classification	Classification procedure
	-	-
16.5.	Relevant H statements (number and full text)	
	H:	H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H332 Harmful if inhaled. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure.
16.6.	Training advice:	-
16.7.	Further information:	** "X" in the product code marks different volumes (different packaging of the product) We are not responsible for consequences in case of failure to comply with instructions for use or improper use of the product described in this material safety data sheet.

ANNEX: Exposure scenario resulting to Chemical safety assessment

-