

Trading name:	OSTEOFAST 2			
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version: 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier	
	Trading name:	OSTEOFAST 2
	Chemical name:	-
	Catalogue number:	OF2-OT-X**
1.2	Relevant identified uses of the substance or mixture and uses advised against	
	Uses:	Decalcifying solution for bone and hard tissue in histology.
	Uses advised against:	Only the identified uses are advised.
	Reason why uses advised against:	The product is intended for use only as an <i>in vitro</i> diagnostic medical device, registered at the Agency for Medicinal Products and Medical Devices and there is no reason to use it for other purposes.
1.3	Details of the supplier of the safety data sheet	
	Supplier:	BioGnost Ltd.
	Address:	Medjugorska 59, Zagreb
	Telephone number:	+385 1 2409997
	Telefax.:	+385 1 2404039
	e-mail of competent person:	msds@biognost.hr
	National contact:	-
1.4	Emergency telephone number	
	National Protection and Rescue Directorate:	112
	Medical information:	+385 1 2348 342
	Other information:	-

SECTION 2. Hazards identification

2.1	Classification of the substance or mixture	
2.1.1	Classification according to Regulation (EC) No 1272/2008 (CLP)	
	Hazard class and category code:	Hazard statements*:
	Skin Corr. 1B	H314
	Eye Dam. 1	H318
2.1.2.	Additional information	
	-	
*For full text of Hazard- and EU Hazard-statements: see SECTION 16		
2.2	Label elements	
	Product identification:	OSTEOFAST 2
	Identification number:	-
	Authorization number:	-

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

Hazard pictograms:	
	GHS05
Signal word:	Danger
Hazard statements:	H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage
Precautionary statements:	P280 Wear protective gloves/protective clothing/eye/protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/attention.
Supplemental hazard information (EU):	EUH071 Corrosive to the respiratory tract.
2.3	Other hazards
	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3. Composition/information on ingredients

CAS/ EC/ Index number	REACH Registration No	Weight % content (or range)	Identification name	Classification according to Regulation (EC) No 1272/2008 (CLP)	Note
64-18-6/ 200-579-1/ 607-001-00-0	-	10 – 13%	formic acid	Flam. Liq. 3; H226 Met. Corr. 1; H290 Acute. Tox. 4; H302 Skin corr. 1A; H314 Eye Dam. 1; H318 Acute. Tox. 3; H331 EUH071	B

Specific concentration limits

Formic acid

Flam. Liq. 3; H226: C>85%	Skin Irrit. 2; H315: 2%≤C<10%
Skin Corr. 1 A; H314: C≥90%	Eye Dam. 1; H318: C>10%
Skin Corr. 1 B; H314: 10%≤C<90%	Eye Irrit. 2; H319: 2%≤C<10%

Trading name:	OSTEOFAST 2			
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version: 9

Note:

B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

SECTION 4. First aid measures

4.1	Description of first aid measures	
	General notes:	If the suggested first aid measures do not prove sufficient, seek medical attention.
	Following inhalation:	Carry the afflicted person out of the contaminated area into a well-ventilated area or out for fresh air. In case of difficult breathing, provide the afflicted person with oxygen.
	Following skin contact:	Remove contaminated clothing. Immediately wash with plenty of water for at least 20 minutes. Seek medical assistance if the symptoms of irritation remain.
	Following eye contact:	Rinse out with plenty of water with the eyelid held wide open for at least 20 minutes. If the symptoms remain, immediately call in ophthalmologist.
	Following ingestion:	Rinse the oral cavity, drink 1-2 glasses of water. Do not induce vomitig. Immediately consult a physician and show the container or label. In case of swallowing large quantities, transport the afflicted person to the hospital.
	Self-protection of the first aider:	-
4.2	Most important symptoms and effects, both acute and delayed	
	Following inhalation:	Depending on concentration and exposure time, it may lead to mucosa irritation, cough, and dyspnea.
	Following skin contact:	Depending on concentration and exposure time, it may lead to irritation, rash, skin drying and skin cracking.
	Following eye contact:	Depending on concentration and exposure time, it may lead to irritation, tearing, redness and pain.
	Following ingestion:	Depending on concentration and exposure time, it may lead to stinging and digestive mucus damage, abdominal pain, nausea, vomiting.
4.3	Indication of any immediate medical attention and special treatment needed	
	-	

SECTION 5. Firefighting measures

5.1	Extinguishing media
-----	---------------------

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

	Suitable extinguishing media:	Small fire - water spray, dry powder, CO ₂ Large fire - water spray or alcohol-resistant foam
	Unsuitable extinguishing media:	No information available
5.2	Special hazards arising from the substance or mixture	
	Hazardous combustion products:	No information available
5.3	Advice for firefighters	
	Use a self-contained open-circuit compressed air breathing apparatus and fireproof clothing.	
5.4	Additional information	
	Do not contaminate the environment with extinguishing media.	

SECTION 6. Accidental release measures		
6.1	Personal precautions, protective equipment and emergency procedures	
6.1.1.	For non-emergency personnel	
	Protective equipment:	Use personal protective equipment (see Section 8).
	Accident prevention methods:	Evacuate members of all non-essential personnel and those members without protective equipment. Avoid breathing vapors and avoid contact with skin and eyes. Do not smoke.
	Emergency procedures:	Mark the area using proper signs.
6.1.2.	For emergency responders:	
	Use protective equipment; in case of inadequate ventilation use adequate airways protective equipment (see Section 8).	
6.2	Environmental precautions:	
	Do not dispose of in sewage, drainage system and waterways. In case of large spillage contact National Protection and Rescue Directorate (NPRD) on 112.	
6.3	Methods and material for containment and cleaning up	
6.3.1.	Bundling, covering of drains; capping procedures:	Sand or clay barriers.
6.3.2.	Cleaning up:	Where possible, the substance can be absorbed by using absorbing material. Place the waste material in tightly closed impermeable containers. Store the substance in well ventilated storage rooms until disposal. Submit for disposal to the legal persons authorized by the Ministry of Environmental and Nature Protection. After disposal of the products, wash the area and involved materials with water.
6.3.3.	Other information:	Do not use incompatible materials (see Section 10).
6.4	Reference to other sections	
	See Section 7 for information about secure handling. See Section 8 for information about personal protective equipment. See Section 13 for information about containment.	

Trading name:	OSTEOFAST 2			
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version: 9

SECTION 7. Handling and storage

7.1	Precautions for safe handling	
7.1.1.	Protection measures	
	Measures to prevent fire:	Use in well ventilated storage rooms.
	Measures to prevent aerosol and dust generation:	Secure proper ventilation.
	Measures to protect the environment:	Prevent spilling into the sewage system and waterways.
	Other measures:	-
7.1.2.	Advice on general occupational hygiene:	
	Do not eat, drink or smoke in the workspace. Thoroughly wash hands after work and before eating.	
7.2	Conditions for safe storage, including any incompatibilities	
	Technical measures and storage conditions:	Keep in tightly closed and upright set containers in a well ventilated storage rooms at temperatures ranging from 15 to 25 °C.
	Packaging materials:	Manufacturer's original packaging.
	Requirements for storage rooms and vessels:	Keep away from food and drink. Keep the containers tightly closed.
	Advices for storage equipment:	The storage must be made of hard material; floors must be resistant to chemicals. There must be no drain that directly leads into sewage system. Secure proper ventilation.
	Further information on storage conditions:	Do not place the unused material in the storage room and do not use empty containers for storing other chemicals. Do not store with incompatible materials (see Section 10).
7.3	Specific end use(s)	
	Recommendations:	-
	Industrial sector specific solutions:	-

SECTION 8. Exposure controls/personal protection

8.1	Control parameters			
Substance	CAS No	Occupational exposure limit values/short term values		Biological limit values
		Ppm	mg/m ³	
Formic acid	64-18-6	5/-	9/-	-
Substance name:	-			

Trading name:	OSTEOFAST 2			
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version: 9

EC No:	-	CAS No:	-	
--------	---	---------	---	--

DNEL

(Industrial)

Route of exposure:	Acute effect local	Acute effect systemic	Chronic effect local	Chronic effect systemic
Oral	-	-	-	-
Inhalation	-	19 mg/m ³ (formic acid)	-	9.5 mg/m ³ (formic acid)
Dermal	-	-	-	-

Critical physical parameters: solubility, flammability, corrosivity: -

Consumer

Route of exposure:	Acute effect local	Acute effect systemic	Chronic effect local	Chronic effect systemic
Oral	-	-	-	-
Inhalation	-	9.5 mg/m ³ (formic acid)	-	3 mg/m ³ (formic acid)
Dermal	-	-	-	-

PNEC

Environmental protection target	PNEC
Fresh water	2 mg/l (formic acid)
Freshwater sediments	13.4 mg/l (formic acid)
Marine water	0.2 mg/l (formic acid)
Marine sediments	1.34 mg/l (formic acid)
Food chain	No information available
Microorganisms in sewage treatment	No information available
Soil (agricultural)	1.5 mg/kg (formic acid)
Air	No information available

8.2	Exposure controls	
8.2.1.	Appropriate engineering controls	
	Substance/mixture related measures to prevent exposure during identified uses:	Use the product in well ventilated rooms. Use personal protective equipment. Do not eat, drink or smoke in the workspace.
	Structural measures to prevent exposure:	In accordance with Section 7.

Trading name:	OSTEOFAST 2			
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version: 9

	Organisational measures to prevent exposure:	Organization of work in order to reduce other worker's influence during work process.
	Technical measures to prevent exposure:	Secure proper workspace ventilation in order to keep concentration levels in air below permitted levels. Secure stations for rinsing eyes and showering.
8.2.2.	Personal protection equipment	
8.2.2.1.	Eye and face protection:	Safety glasses that stick to face (EN 166) or visor in case of lower levels of concentration in air; protective gas mask that covers the entire face in case of higher levels of concentration in air.
8.2.2.2.	Skin protection	
	Hand protection:	The protective gloves have to satisfy the specification of Regulation (EU) 2016/425 and the related standard EN374. Glove material: butyl rubber Glove thickness: 0.70 mm Time until perforation: > 480 min
	Other skin protection:	Wear antistatic clothing made of natural fibers (such as cotton) with long sleeves (EN 13688) and shoes that cover the entire foot.
8.2.2.3.	Respiratory protection:	Suitable mask (EN 136) equipped with a "A" filter (EN 14387) used when concentration levels exceed GVI.
8.2.2.4.	Thermal hazards:	No information available
8.2.3.	Environmental exposure controls	
	Substance/mixture related measures to prevent exposure:	See Section 6
	Structural measures to prevent exposure:	Use modern equipment.
	Organisational measures to prevent exposure:	Adapt the work process to the required working conditions of the workplace.
	Technical measures to prevent exposure:	See Section 6

SECTION 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

		Value	Method
	Physical state:	liquid	No information available
	Color:	light yellow	No information available
	Odour/odour threshold:	sharp/no information available	No information available
	Melting point / freezing point:	No information available	No information available

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

	Boiling point or initial boiling point and boiling range:	No information available	No information available
	Flammability:	No information available	No information available
	Lower and upper explosion limit:	No information available	No information available
	Flash point:	No information available	No information available
	Auto-ignition temperature:	No information available	No information available
	Decomposition temperature:	No information available	No information available
	pH:	No information available	No information available
	Kinematic viscosity:	No information available	No information available
	Solubility:	No information available	No information available
	Partition coefficient n-octanol/water (log value):	No information available	No information available
	Vapour pressure:	No information available	No information available
	Density and/or relative density	No information available	No information available
	Relative vapour density:	No information available	No information available
	Particle characteristics:	No information available	No information available
9.2	Other information		
	-		

SECTION 10. Stability and reactivity

10.1	Reactivity:	See subsections 10.3 through 10.5.
10.2	Chemical stability:	The product is chemically stable under standard ambient conditions of storing and using (room temperature).
10.3	Possibility of hazardous reactions:	Alkaline hydroxides, aluminum, oxidizing agents, nitric acid, sulfuric acid.
10.4	Conditions to avoid:	Sources of heat, sparks, ignition, and heating.
10.5	Incompatible materials:	Iron, zinc.
10.6	Hazardous decomposition products:	Carbon monoxide.

SECTION 11. Toxicological information

11.1	Information on hazard classes as defined in Regulation (EC) No 1272/2008				
	Acute toxicity:				
Route of exposure:	Method	Species	Dose LD ₅₀ /LC ₅₀ or ATE _{mix}	Exposure time	Results
Oral:	-	rat (formic acid)	LD ₅₀	-	730 mg/kg
Dermal:	-	-	-	-	-
Inhalation:	-	rat (formic acid)	LC ₅₀	4h	7.85 mg/l

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

Specific target organ toxicity – single exposure (STOT SE):						
	Specific effects			Target organ		Note
Oral:	No information available			No information available		-
Dermal:	No information available			No information available		-
Inhalation:	No information available			No information available		-
Aspiration hazard:			No information available.			
Irritation and corrosion						
Exposure time		Species		Evaluation	Method	Note
Skin corrosion/irritation:	-	rabbit		-	-	causes severe burns
Serious eye damage/irritation	-	-		-	-	cause eye damage
Sensitization						
Skin sensitization:		No information available				
Respiratory sensitization:		No information available				
Symptoms related to the physical, chemical and toxicological characteristics						
Oral exposure:		Damage to gastrointestinal tract, acid-basic balance disorders, damage to blood and kidneys.				
Dermal exposure:		Irritating and corrosive effects for skin.				
Inhalation exposure:		Irritating and corrosive effects for airways.				
Eye exposure:		Danger of permanent eye damage.				
Repeated dose toxicity (subacute, subchronic, chronic)						
	Dose	Exposure time	Species	Method	Evaluation	Note
Subacute oral	No information available	No information available	No information available	No information available	No information available	-
Subacute dermal	No information available	No information available	No information available	No information available	No information available	-

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

Subacute inhalation	No information available	No information available	No information available	No information available	No information available	-
Subchronic oral	No information available	No information available	No information available	No information available	No information available	-
Subchronic dermal	No information available	No information available	No information available	No information available	No information available	-
Subchronic inhalation	No information available	No information available	No information available	No information available	No information available	-
Chronic oral	No information available	No information available	No information available	No information available	No information available	-
Chronic dermal	No information available	No information available	No information available	No information available	No information available	-
Chronic inhalation	No information available	No information available	No information available	No information available	No information available	-

Specific target organ toxicity – repeated exposure (STOT RE):

	Specific effects	Target organ	Note
Subacute oral	No information available	No information available	-
Subacute dermal	No information available	No information available	-
Subacute inhalation	No information available	No information available	-
Subchronic oral	No information available	No information available	-
Subchronic dermal	No information available	No information available	-
Subchronic inhalation	No information available	No information available	-
Chronic oral	No information available	No information available	-
Chronic dermal	No information available	No information available	-
Chronic inhalation	No information available	No information available	-

CMR effects (carcinogenicity; mutagenicity; reproductive toxicity)

Carcinogenicity:	No information available
Mutagenicity <i>in vitro</i> :	No information available
Genotoxicity:	No information available
Mutagenicity <i>in vivo</i> :	No information available

Trading name:	OSTEOFAS 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

	Germ cell mutagenicity:	No information available
	Reproductive toxicity:	No information available
	Summary of evaluation of the CMR properties:	No information available
11.2.	Information on other hazards:	
11.2.1.	Endocrine disrupting properties:	
	No known endocrine disrupting properties that affect human health.	
11.2.2.	Other information:	
	-	

SECTION 12. Ecological information						
12.1	Toxicity					
Acute (short-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish	LC ₅₀	96 hours	fish	-	130 mg/l (formic acid)	-
Crustacea:	EC ₅₀	48 hours	Daphnia magna	-	365 mg/l (formic acid)	-
Algae/aquatic plants	IC ₅₀	3 days	algae	-	1,24 mg/l (formic acid)	-
Other organisms	-	-	-	-	-	-
Chronic (long-term) toxicity	Dose	Exposure time	Species	Method	Evaluation	Note
Fish	LC ₅₀	96 hours	No information available	No information available	No information available	-
Crustacea:	EC ₅₀	48 hours	No information available	No information available	No information available	-
Algae/aquatic plants	IC ₅₀	72 hours	No information available	No information available	No information available	-
Other organisms	-	-	-	-	-	-
12.2	Persistence and degradability					

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

Abiotic degradation				
	Degradation half-lives	Method	Evaluation	Note
Marine water	No information available	No information available	No information available	-
Fresh water	No information available	No information available	No information available	-
Air	No information available	No information available	No information available	-
Soil	No information available	No information available	No information available	-

Biodegradation				
% Degradation	Time (days)	Method	Evaluation	Note
No information available	No information available	No information available	No information available	No information available

12.3	Bioaccumulative potential					
	Octanol-water partition coefficient (log Kow)					
Value	Concentration	pH	°C	Method	Evaluation	Note
-	-	-	-	-	-	-

Bioconcentration factor (BCF)				
Value	Species	Method	Evaluation	Note
No information available	No information available	No information available	No information available	-

Chronic ecotoxicity						
Value	Dose	Exposure time	Species	Method	Evaluation	Note
Chronic toxicity on fish	LC ₅₀	No information available	No information available	No information available	No information available	-

Trading name:	OSTEOFAST 2					
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9	

Chronic toxicity on crustacea (<i>Daphnia</i>)	EC ₅₀	No information available	No information available	No information available	No information available	-
--	------------------	--------------------------	--------------------------	--------------------------	--------------------------	---

12.4 Mobility in soil

Known or predicted distribution in environmental compartments:					
No information available					
Surface tension:					
	Value	°C	Concentration	Method	Note
	No information available	No information available	No information available	No information available	-

Adsorption / desorption

Transport	A/D coefficient Henry's constant	log K _{ow}	Evaporation rate	Method	Note
Soil-water	No information available	No information available	No information available	No information available	-
Water-air	No information available	No information available	No information available	No information available	-
Soil-air	No information available	No information available	No information available	No information available	-

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.					
--	--	--	--	--	--

12.6 Endocrine disrupting properties

Substance/mixture does not contain components considered to have endocrine disruption according to Article 57(f), regulation on registration, assessment, approval and restricting chemicals (REACH), or delegated Regulation (EU) 2017/2100 or (EU) 2018/605 at levels of 0.1% or above.					
---	--	--	--	--	--

12.7 Other adverse effects

No adverse effects are expected.					
----------------------------------	--	--	--	--	--

SECTION 13. Disposal considerations

Trading name:	OSTEOFAS 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

13.1	Waste treatment methods
13.1.1.	Product/Packaging disposal:
	Submit for disposal to the legal person authorized by the Ministry of Environmental and Nature Protection.
13.1.2.	Waste codes/waste designations according to Law:
	15 01 10*: Packaging that contains residual hazardous substances or is contaminated with hazardous substances
13.1.3.	Waste treatment – relevant information:
	No information available
13.1.4.	Sewage disposal – relevant information:
	Waste must not be disposed of into the sewage system.
13.1.5.	Other disposal recommendations:
	Do not dispose of the product's remains into the sewage system. Submit the remains to the collectors authorized by the ministry in charge. Do not dispose of the packaging into the sewage system. Submit the packaging to the collectors authorized by the ministry in charge.
13.1.6.	Relevant Community provisions:
	-

SECTION 14. Transport information

	Transporting/shipment by road (ADR)
UN number:	3265
UN proper shipping name:	Corrosive liquid, acidic, organic, n.o.s. (Formic acid)
Transport hazard class(es):	8
Packing group:	III
Environmentally hazardous:	No
Special precautions for user:	-
	Transporting/shipment by rail (RID)
UN number:	3265
UN proper shipping name:	Corrosive liquid, acidic, organic, n.o.s. (Formic acid)
Transport hazard class(es):	8
Packing group:	III

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

Environmentally hazardous:	No
Special precautions for user:	-
Inland waterway transport (ADN)	
UN number:	3265
UN proper shipping name:	Corrosive liquid, acidic, organic, n.o.s. (Formic acid)
Transport hazard class(es):	8
Packing group:	III
Environmentally hazardous:	No
Special precautions for user:	-
Transporting/shipment by sea (IMDG)	
UN number:	3265
UN proper shipping name:	Corrosive liquid, acidic, organic, n.o.s. (Formic acid)
Transport hazard class(es):	8
Packing group:	III
Environmentally hazardous:	No
Special precautions for user:	-
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code:	-
Transporting/shipment by air (ICAO-TI/IATA-DGR)	
UN number:	3265
UN proper shipping name:	Corrosive liquid, acidic, organic, n.o.s. (Formic acid)
Transport hazard class(es):	8
Packing group:	III
Environmentally hazardous:	No
Special precautions for user:	-
Further information:	

SECTION 15. Regulatory information

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	
	EU regulations	
	Authorization and/or restrictions of use	
	Authorizations:	-
	Restrictions:	-

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

	Other EU regulations:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC; Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC; Council Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work; Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006; REACH Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII);
	Information according 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline)	
	National legislation:	Chemicals Act, Regulation on classification, packaging and labeling of dangerous substances, Ordinance on occupational exposure limit values and on biological limit values, Regulation on categories, types and classification of waste with a waste catalog and list of hazardous waste, Ordinance on writing Material safety data sheet, Transport of Hazardous Substances Act
15.2	Chemical safety assessment	
	None	

SECTION 16. Other information		
16.1	Indication of changes:	-
16.2	Abbreviations and acronyms:	ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative
16.3.	Key literature references and source of data:	-

Trading name:	OSTEOFAST 2				
Product code:	OF2-OT-X**	Revision date:	18 March 2026	Version:	9

16.4.	Classification and procedure used to derive the classification for mixture according to Regulation (EC) 1272/2008 (CLP)	
	Classification	Classification procedure
	-	-
16.5.	Relevant H statements (number and full text)	
	H: 226	Flammable liquid and vapour.
	290	May be corrosive to metals.
	302	Harmful if swallowed.
	314	Causes severe skin burns and eye damage.
	318	Causes serious eye damage.
	331	Toxic if inhaled.
	EUH071	Corrosive to the respiratory tract.
16.6.	Training advice:	-
16.7.	Further information:	** "X" in the product code marks different volumes (different packagings of the product) We are not responsible for consequences in case of failure to comply with instructions for use or improper use of the product described in this material safety data sheet.

ANNEX: Exposure scenario resulting to chemical safety assessment
-

Version	Description / reason of change	Date
9.	Alignment with Commission Delegated Regulation (EU) 2024/2564	18.03.2026.